

FC Fiber Patch cord

Features

- Compliance with IEC, JIS, Telcordia
- Threaded, key-oriented coupling mechanism which allows repeatable, low-loss connections
- Simplex, duplex, and multi-fiber assemblies available in standard and custom configurations
- Singlemode and Multimode
- PC or APC finish

Applications

- CATV
- Metro Applications
- Active device termination
- Test equipment
- Wide Area Networks (WANs)
- Telecommunication networks
- Local Area Networks (LANs)
- Data processing networks
- Premise installations



Specifications (Patch cord / Pigtail / Connector)

ITEM	SM / PC	SM / APC	Multi Mode
Insertion Loss(dB)	< 0.2	< 0.2	< 0.3
Return Loss(dB)	> 40	> 60	-
Durability:500matings(dB)	< 0.2	< 0.2	< 0.2
Ferrule Type	Standard	Step / Conical	Standard
Body Material	Nickel plated brass		
Cable	0.9 / 2.0 / 2.4 / 3.0 / Zip Cable		
Boot Type	Variety of Color , Design available		

Specifications (Adapter)

ITEM	SM / PC	SM / APC	Multi Mode
Sleeve	Ceramic/ Phosphor bronze	Ceramic	Phosphor bronze
Body Material	Nickel plated brass		
Body Type	Square Type / Round Type		