

## SC Fiber Connector

### Features

- NTT-SC compatibility
- Low insertion loss and back reflection
- One-piece construction and pull-proof design
- Free-floating pre-radiused ceramic ferrule
- Precision anti-rotation key
- Corrosion resistant body
- UL-rated plastic housing and boots in a variety of colors

### Applications

- CATV
- Active device termination
- Test equipment
- Telecommunication networks
- Multimedia
- Premise installations



## Specifications

ITEM	SM / PC	SM / APC	Multi Mode
Insertion Loss(dB)	< 0.2	< 0.2	< 0.3
Return Loss(dB)	> 40	> 60	-
Durability:500matings(dB)	< 0.2	< 0.2	< 0.2
Ferrule Type	Standard	Step / Conical	Standard
Cable	0.9 / 2.0 / 2.4 / 3.0 / Zip Cable		
Boot Type	Variety of Color , Design available		

### LEAD Fiber Optics Co.,Ltd.

TEL: 886-2-8672-2371

[www.twfiberoptic.com](http://www.twfiberoptic.com)

FAX: 886-2-8672-3275

[sales@fiberoptic.com.tw](mailto:sales@fiberoptic.com.tw)

3F., No.135, Dasyue Rd., Sansia Township, Taipei County 23741, Taiwan (R.O.C.)

**Lfo**